

1
2
3
4
5
6
7
8
9
10
11
12
13

UNITED STATES PATENT APPLICATION
FOR
METHOD, COMPUTER SYSTEM AND COMPUTER PROGRAM PRODUCT FOR
PRINTING A DOCUMENT PAGE

Inventor:

Thomas Trenz

FIELD OF THE INVENTION

The present invention relates generally to computing systems provided with printing functionalities, and more particularly to a method, a computer system and a computer program product for printing a document page on one sheet or split over several sheets.

BACKGROUND OF THE INVENTION

Although documents generated by computer programs are more and more stored and transmitted in the form of computer-readable digital data, computer systems will still have, even in the long term, the ability to produce printouts of such documents on paper sheets.

Early personal computer printers could, for the most part, only print characters. Functions like the positioning and definition of margins and fonts were indicated by special codes sent by the personal computer. The codes for printers from different manufacturers were incompatible with each other, and each application program had a different set of printer drivers with those codes embedded. A printer driver is a special purpose program that typically processes printer-independent printing information to printer-dependent printing information usable by the corresponding printer to produce printouts. As software became more capable - word processors, presentation graphics, and page layout programs in particular - this technique became impractical. Different application programs had a different set of drivers. If a user bought a new printer, he had to get new drivers from each of his software vendors. The software vendors had to create and maintain their printer driver libraries.

1 Modern operating systems, like Windows (Windows is a trademark of
2 Microsoft Corporation) simplified this problem, because they provided a printer-
3 independent interface between application programs and the printers. In the
4 Windows operating system, the application program draws on a page through
5 the same interface provided by the operating system it uses to draw on a
6 computer screen, the graphics device interface (GDI). The GDI then sends
7 commands to the printer driver, which translates into the language the printer
8 understands and, with the help of a communications port driver, sends the
9 result to the printer.

10 In order to reduce the processing load on the computer and the transfer
11 load when printing over a network, for the most part, printer drivers use what
12 is called a page description language to communicate what is required to the
13 printer. Two page description languages are widely used: PostScript (developed
14 by Adobe) and PCL (developed by Hewlett-Packard) (PostScript and Adobe are
15 trademarks of Adobe Systems Incorporated, and PCL and Hewlett-Packard are
16 trademarks of Hewlett-Packard Corporation). Notwithstanding the fact that
17 many printer manufacturers have standardised on PCL or PostScript, printer
18 drivers specific to the respective printer are still needed. This is mainly because
19 the printer drivers allow the control options and features in the printers, and the
20 controls for them are not standardised. Most Windows printer drivers are based
21 on a core printer driver, developed by Microsoft (Microsoft is a trademark of
22 Microsoft Corporation), that handles things like rendering fonts, choosing the
23 port the printer is connected to, and otherwise performing the tasks needed to
24 send a page to the printer. The printer manufacturer builds tables that tell the
25 core driver how to accomplish the necessary functions, and adds functions, for
26 example related to colour matching, paper handling, and maintenance (Barry
27 Press et al.: PC Upgrade and Repair Bible, 2000, third edition, pages 746-749).

28 Since modern application programs provide the user with many ways to
29 print a document, the need has arisen to be able to visually check the desired

1 printout of the document before the user proceeds to make the actual printout.
2 Therefore, many application programs can provide the user with a print preview
3 on the screen of the computer system. A print preview functionality can now
4 even be implemented on the level of the Windows operating system by using
5 the object-oriented Microsoft Foundation Class library, better known by the
6 acronym MFC (Jeff Prosise: Programming Windows with MFC, second edition,
7 1999, pages 759-801). The Windows operating system and MFC allow a
8 preview of the document to be printed even if the application program that has
9 generated the document has no preview functionality. In order to make sure
10 that the preview of the document to be printed looks exactly like the
11 subsequent actual printout, it is known from EP 0 933 692 A2 assigned to
12 Hewlett-Packard Company that the printer driver (rather than the application
13 program) provides the print preview.

14 In the known print previews, the user can actuate buttons for going to
15 the next or the previous page, switching between one-page and two-page
16 views, zooming in and out, and so on. However, he can not modify what will
17 be printed. If he is satisfied with what is presented, the user may click a print
18 button to have the corresponding print job processed further and sent to the
19 printer to produce an actual print-out. However, if the user wants to modify
20 what will be printed, he has to actuate a cancel button to discontinue the
21 printing process at this point and return to a previous step in the printing
22 process or to the application program where the necessary modifications can
23 be carried out.

24 For many applications of computer systems, there is a need to generate
25 pages which are too large to fit on one sheet of paper, in particular, on a sheet
26 of paper in a format usually used for correspondence, for example DIN A4
27 (210x297mm) or US-Letter (8.5x11inch), called "note paper" hereinafter. Such
28 a page can be, for example, a construction drawing generated by a CAD
29 application program. If such a drawing were scaled down to fit on one note

1 paper sheet the necessary details of the drawing would not be visible any
2 more.

3 A possible solution is the use of special printers for large paper sheets,
4 for example, plotters for DIN A1 sheets (59.4x84cm). Another solution, in
5 situations where such a special printer is not available, is to split the page into
6 several smaller parts and to print them on note paper sheets subsequently. The
7 separately printed sheets can then be put together like tiles so as to form a
8 large-scale printout of the page. Normally, such a tile-like printing functionality
9 is implemented on the level of an application program, but it is also known from
10 EP 0 933 692 A2 to implement it on the level of a printer driver.

11 A typical application where large pages are generated and have to be
12 printed is architectural software, for instance the program ArchiCAD 6.0
13 (ArchiCAD is a trademark of Graphisoft Corporation). The ArchiCAD 6.0
14 program allows the user to choose a paper format and print scale. Depending
15 on the user's choice, the program can split a page into several printout sheets.
16 It displays a schematic representation of the number of required sheets as well
17 as the effective print region on these sheets.

18 EP 0 933 692 A2, which has already been mentioned above, discloses a
19 special printer feature called "BillBoard 2X2". The choice of this feature by a
20 user causes the printer driver to process a print job for a page to be printed on
21 one sheet into a print job for a four-sheet printout. This printout can be viewed
22 in a preview window exactly as it will be printed. If the user decides to change
23 a printing feature after inspecting the preview window, for example, to change
24 from a four-sheet printout to a one-sheet printout or vice versa, he has to
25 actuate a cancel print button and to return to a previous window where he can
26 make the corresponding settings.

27 SUMMARY OF THE INVENTION

28

29

1 A method performed by a computer system prints a document page on
2 one sheet or split over several sheets. The method comprises the steps of:
3 simultaneously displaying on a computer display a preview of the document
4 page as it will be printed, including displaying sheet splitting, and at least one
5 control element for modifying the print scale or the number of sheets;
6 dynamically changing the displayed sheet splitting in response to a
7 corresponding actuation of the control element; printing the document page
8 according to the displayed sheet splitting upon receiving a print command.

9 According to another aspect, a computer system comprises a processing
10 unit and storage for processing programs and program components, a computer
11 display, a printer and an application program for creating at least one document
12 page. The program component causes a print preview of the document page,
13 including sheet splitting, and at least one control element for modifying a print
14 scale or the number of sheets to be simultaneously displayed on the computer
15 display, further causes the displayed sheet splitting to dynamically change in
16 response to a corresponding actuation of the control element, and causes the
17 document page to be printed according to the displayed sheet splitting upon
18 receiving a print command.

19 According to still another aspect, a computer program product includes
20 program code for carrying out the following method for printing a document
21 page on one sheet or split over several sheets, when executed on a computer
22 system. The method comprises: simultaneously displaying on a computer
23 display a preview of the document page as it will be printed, including
24 displaying sheet splitting, and at least one control element for modifying the
25 print scale or the number of sheets; dynamically changing the displayed sheet
26 splitting in response to a corresponding actuation of the control element;
27 causing the document page to be printed according to the displayed sheet
28 splitting upon receiving a print command.

1 Other features are inherent in the disclosed method, computer system
2 and computer program product or will become apparent to those skilled in the
3 art from the following detailed description of embodiments and its
4 accompanying drawings.

5 6 DESCRIPTION OF THE DRAWINGS

7
8 In the accompanying drawings:

9 FIG. 1 shows a print preview of a document page to be printed on eight
10 sheets in a vertical format;

11 FIG. 2 shows a print preview as in FIG. 1, with the document page to be
12 printed on two sheets;

13 FIG. 3 shows a print preview as in FIG. 1, with the document page to be
14 printed on one sheet;

15 FIG. 4 shows a print preview as in FIG. 1, with the document page to be
16 printed on six sheets in a landscape format;

17 FIG. 5 schematically depicts a page location identification;

18 FIG. 6 schematically depicts a computer system on which a print preview
19 method is executed;

20 FIG. 7 is a schematic representation of how a print job is processed
21 under the Windows operating system;

22 FIG. 8 is a flow diagram of a method to print a document page wherein a
23 print preview functionality is implemented by an application program;

24 FIG. 9 is a flow diagram of a method to print a document page wherein a
25 print preview functionality is implemented by a printer driver;

26 FIG. 10 is a class diagram of a part of a computer program for carrying
27 out the methods of FIG. 7 and 8.

28 29 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

1
2 Functional aspects of preferred embodiments will be described with
3 reference to FIG. 1 to 5, and structural aspects with reference to FIG. 6 to 10.
4 Before proceeding further with the description, however, a few terms will be
5 defined.

6 The term "sheet" mainly refers to a paper sheet on which a printer prints
7 a printout. Preferably, the paper sheets have note-paper format. However, it is
8 likewise possible to print in a file rather than on paper. In this case, a "sheet" is
9 that part of the print file which corresponds to what is printed on a paper sheet
10 when the print file is actually printed on paper. Thus, the term "sheet" refers to
11 a physical object - a paper sheet - or to that part of a print file which directly
12 corresponds to such a physical object.

13 In contrast, the term "page" refers to a virtual object. It is that part of a
14 document represented by digital data which represents information that shall be
15 viewable together in one view, for example a construction drawing, a network
16 map, a class diagram, a business drawing or a business diagram. (In the
17 particular case where the document consists of only one page, the term "page"
18 refers to the whole document). If a page is smaller than or equal to the sheet
19 size, it can be printed on one sheet. However, if it is larger than the sheet size,
20 only parts of it can be printed on the sheets.

21 In some preferred embodiments the print preview method is implemented
22 by an application program, normally an application program which generates or
23 handles documents to be printed. In these implementations the print preview
24 method is limited to the respective application program and usually cannot be
25 shared between different application programs. However, if the print preview
26 method is implemented by a printer driver or an operating system, as in other
27 preferred embodiments, the "tile-like" printing functionality can be provided
28 even if application programs are used which do not allow a page to be split into

several sheets. Further, the "look and feel" of the tile-like printing functionality is then the same for all applications.

Normally, a job to printout a document page generated by an application program is initiated by that application program. It draws on a page through an interface provided by the operating system which, in turn, sends commands to a printer driver, which translates these into the language the printer understands and sends the results to the printer via a communication port driver. Usually, when an application program generates a document to be printed, the graphical representation, i.e. the arrangement and presentation of the page information depends on the sheet size. (In certain application programs, like word processors, even the decision as to what belongs to a certain page depends on the sheet size). Therefore, normally the sheet size has to be defined before an application program can prepare a page for the printout and pass the print job to the operating system. If the disclosed print preview method is implemented by the printer driver or the operating system, the page size definition used by the application program generally differs from the total size of the "tile-like" sheets on which the page is printed, since the user can modify the print scale and/or the number of sheets after the application program has passed the print job to the operating system. Preferably, a program that initiates a print job uses a virtual sheet size which is larger than the actual sheet size. Most preferably, the virtual sheet size is at least equal to the total size of the largest possible number of sheets to be used for printing a document in the disclosed tile-like printing method. For example, if the maximum number of sheets is eight and these sheets are arranged as shown in FIG. 1 (two rows of four sheets), the virtual sheet size for DIN A4 sheets would be at least 840x594mm. When the print job is passed to the printer driver or the operating system, the disclosed print preview method is carried out using a representation of the page adapted to that virtual sheet size as an input. If the virtual sheet size chosen is sufficiently large, the disclosed print

1 preview method will then only scale down the representation of the page
2 drawn on the virtual sheet by the application program. However, it is likewise
3 possible that the application program uses a smaller virtual sheet size, and the
4 printer driver or the operating system scales up the representation of the page
5 drawn on the virtual sheet by the application program.

6 In the embodiments shown the control element with which a user can
7 change the print scale and/or the number of sheets is a graphical slider.
8 Graphical sliders are normally employed to allow a user to scroll a document in
9 a window of a graphical user surface. Although a graphical control element, like
10 the graphical slider is preferred, the control element could alternatively be a
11 non-graphical control element, for example a field where the user can type in
12 the print scale or the number of sheets or a menu from which the user can
13 select these.

14 In the disclosed embodiments, the sheet splitting is displayed by
15 overlaying the preview of the document page with a grid. Each field of the grid
16 corresponds to one sheet. This solution provides the user with an impression of
17 how the tile-like printout will like when the individual sheets are assembled
18 together. Alternatively, the individual sheets can be displayed in the preview
19 with spaces between them.

20 After having printed the individual sheets, the user often wants to
21 assemble the "tiles" to get a printed representation of the entire page. This
22 assemblage may be facilitated by a sheet location identification which is printed
23 on the individual sheets. For example, it is a small graphic which is printed in a
24 corner (e.g. upper left corner) of each page. It identifies the location of the
25 individual sheet in relation to the entire page. For this purpose, in the disclosed
26 embodiments the graphic sketches the sheet splitting of the preview, with the
27 field corresponding to the respective sheet being marked, for example by colour
28 code or grey scale.

1 It may happen that a user wants to use certain sheets of a tile-like
2 printout individually, without the surrounding sheets. Or, it may be desirable
3 not to split a certain detail of a page to be printed into two or more parts since
4 this may degrade the quality of the detail when the "tiles" are assembled.
5 Therefore, in some of the disclosed embodiments, the user can shift the sheet
6 splitting relative to the page by a corresponding actuation of a sheet splitting
7 shift control element (like one or two graphical sliders) or a pointing device (like
8 a "mouse" or a trackball in conjunction with a mouse or trackball pointer).

9 Although the disclosed method is preferably implemented by software, it
10 could likewise be implemented in whole or in part by firmware or hardware
11 without departing from the scope or spirit of the invention.

12 FIG. 1 to 5 show the functional aspects of the disclosed embodiments.

13 FIG. 1 shows a dialog box 1 as it appears on a screen of a computer
14 system described below in more detail. It appears when the user has initiated a
15 print job by giving an application program a corresponding print command. The
16 dialog box 1 is composed of a dialog-box frame 2 surrounding a print preview
17 window 3 in which a print preview 4 is displayed. The print preview 4 shows a
18 graphical representation 5 of a page to be printed. In the example of FIG. 1 to
19 4, it is a representation of what is called a topology map. Such a map shows
20 segments, notes and devices of a network as well as other attached networks.
21 The graphical representation 5 is overlaid with a grid 6 which divides it into
22 several fields 7. Each field 7 represents one sheet of paper printout. Those
23 parts of the graphical representation 5 which lie together within one field 7 will
24 be printed on one sheet. Thus, the grid 6 visualises how the page will be split
25 into several sheets when it is printed. At the left side of the dialog-box frame 2
26 a graphical slider 8 is provided. The user can move it and, thereby, modify the
27 print scale in a quasi-continuous manner. In the example shown in FIG. 1, the
28 slider 8 is shown in its uppermost position which corresponds to a 100% print
29 scale. In the shown 100% print scale, the outer contour of the grid 6

1 corresponds to the edge of the virtual page on which the application program
2 has drawn the graphical representation 5. The dialog-box frame 2 includes
3 further control elements: a print button 9, a cancel button 10 and a close
4 button 11. Upon clicking on the print button, the print job proceeds further and
5 causes a tile-like printout of what has been displayed in the print preview
6 window 3. By clicking on the cancel button 10, the dialog box 1 is closed, and
7 the user is brought back to a previous stage of a print menu or to the
8 application in which the initial print command was given. The function of the
9 close button 11 corresponds to that of the cancel button 10. In the example of
10 FIG. 1, the print preview window 3 is relatively small and, therefore, shows
11 only a part of the document page and the overlaid grid 6. The print preview
12 window 3 can easily be expanded so as to show the entire page, for example
13 by positioning the mouse cursor over the corresponding dialog box frame,
14 depressing the mouse button and dragging the frame edge in a corresponding
15 direction.

16 FIG. 2 shows a print preview of the same document page as shown in
17 FIG. 1, however, scaled down to about 33% of the print scale of FIG. 1. The
18 grid 6 has now only two fields 7 corresponding to two sheets, and the
19 graphical representation 5 of the page (the topology map) fits on these two
20 sheets. The slider 8 is now in a lower position, about 1/3 of the distance
21 between the lowermost and uppermost positions above the lowermost position.
22 In other embodiments (not shown) the correspondence between slider position
23 and scale factor is not proportional; then, the slider position might be in the
24 middle between the upper most and lower most positions at 30% print scale.
25 The transition from the print scale of FIG. 1 to the one of FIG. 2 is performed
26 by a user who pulls down the slider 8 by means of a pointing device. In
27 response to the continuous downward movement of the slider 8, the graphical
28 representation 5 continuously becomes smaller, whereas the size of the fields 7
29 remains constant. As soon as the actual size of the graphical representation 5

1 requires a smaller number of sheets, the number of sheets jumps automatically
 2 to the smaller value then required, i.e. the corresponding fields of the grid 6
 3 disappear. For example in the transition from FIG. 1 to FIG. 2 at first the
 4 number of fields 7 per row decreases from four to three, resulting in a decrease
 5 in the number of fields 7 from eight to six. Then, the number of rows decreases
 6 from two to one, resulting in a decrease in the number of fields 7 from six to
 7 three. Finally, the number of fields 7 in the remaining row decreases from three
 8 to two. The continuous decrease in the print scale and the discontinuous
 9 decrease in the number of fields 7 happens dynamically in correspondence to
 10 the actuation of the slider 8 which is part of the preview dialog box 1, while
 11 the user can inspect the preview. Thus, the user does not need to go to any
 12 other dialog box, let alone to cancel or close the print preview dialog box 1.

13 If the slider 8 is pulled down further to a position corresponding to, say,
 14 17% print scale, the size of the graphical representation 5 is continuously
 15 reduced to that scale, and the number of fields 7 decreases from two to one
 16 without changing the field size. The result is shown in FIG. 3. The graphical
 17 representation 5 of the page now only takes up a part of the field 7 (here: the
 18 upper half of it). A further reduction of the print scale is possible, which
 19 reduces the part of the field 7 occupied by the graphical representation 5. In
 20 the non-occupied part of field 7 the printed sheet remains blank.

21 FIG. 4 shows a dialog box 1 which corresponds to the dialog box of FIG.
 22 1 to 3 and which offers the user additional functions. One of these additional
 23 functions is the possibility to switch between vertical sheet format (as in FIG. 1
 24 to 3) and horizontal sheet format (also known as "landscape" format), as
 25 shown in FIG. 4. The user can switch between these two formats by clicking
 26 on a landscape button 12 located at the lower side of the dialog box frame 2.
 27 Depending on the actual size and format of the document, it may happen that
 28 the number of fields 7 changes when the user switches from one format to the
 29 other. For example, in FIG. 4 the graphical representation 5 (topology map),

1 which is displayed in a 100% print scale, is shown to require only six sheets in
 2 the landscape format, whereas it requires eight sheets in the vertical format of
 3 FIG. 1.

4 The second additional function allows the user to shift the grid 6 relative
 5 to the graphical representation 5. By actuating a horizontal grid displacement
 6 slider 13 the user can achieve a relative displacement in the horizontal
 7 direction, and by actuating a vertical grid displacement slider 14 he can achieve
 8 a relative displacement in the vertical one. The displacements are displayed
 9 dynamically, as the print scale variations, without a need to go to another
 10 dialog box or to close the print preview dialog box 1. The grid displacement
 11 sliders 13, 14 are provided at the upper and right side of the dialog-box frame
 12 2, respectively.

13 FIG. 5 shows a sheet location identification graphic 15 which is printed
 14 on the upper left corner of the sheet corresponding to the middle upper field 7
 15 of the print preview 4 of FIG. 4. It depicts the arrangement of the several
 16 "titles" of the page, here six sheets (two rows of three sheets) in the horizontal
 17 format. The location of the actual sheet in relation to the entire page is
 18 identified by a mark 16 in the corresponding field of the sheet location
 19 identification graphic 15, for example a grey or coloured mark 16. When all
 20 "tiles" of a page have been printed, the user can easily assemble them by
 21 means of the sheet location identification graphic 15 to form a large-scale
 22 printout of the page.

23 FIG. 6 to 10 show structural aspects of the disclosed embodiments.

24 A typical computer system 21 for providing the print preview
 25 functionality of FIG. 1 to 5 is shown in FIG. 6. It comprises a Personal
 26 Computer 22, a display 23 and a printer 24. The Personal Computer 22 is
 27 connected to a network 25, preferably the Internet, and/or has a portable
 28 storage medium reader (PSMR) 26, for example a floppy disk drive or a CD-
 29 ROM drive. It is equipped with a central processing unit 27 (CPU) and storage

28, for example a random access memory (RAM) and a hard disk. A program including program code for carrying out the disclosed method is stored in the storage 28 and is executed by the CPU 27. It can be loaded into the storage 28 from a host in the network 25 or from a portable storage medium by means of the PSMR 26.

FIG. 7 is high-level diagram of how a print job is processed under the Windows operating system. The processing is similar under other operating systems, like Linux. An application program 31 generates a page and starts a print job to print a graphical representation of the page. It draws the page through a graphics device interface (GDI) provided by the Windows operating system 32. The operating system 32 then passes the print job to the printer driver 33 which processes the printer-independent printer information from the operating system 32 to printer-dependent printing information and sends the information via a communications port driver 34 to the printer 24. The operating system 32 uses a page description language, like PostScript or PCL. The disclosed print preview method can be implemented by the application program 31, the operating system 32 or the printer driver 33. Since the implementations in these last two cases are similar, only the first and third possibilities are described in further detail below.

FIG. 8 is a flow diagram which illustrates an implementation by the application program 31. In step 41, a document page is generated, for instance the topology map shown in FIG. 1 to 5. If the user wants to print the page and gives a corresponding print command, a print job is created in step 42, and a printer configuration dialog is opened on the display 23 in step 43. The user has the possibility to cancel the print job in step 44 or to choose a print preview in step 45. If he chooses the print preview, a print preview dialog is opened in step 46. In step 47 the graphical representation 5 of the page and the sheet splitting 6 are determined and displayed in the dialog box 1, on the basis of the set print scale. A default setting of the print scale is 100%. In step

1 47, also a control element for modifying the print scale (the slider 8) is
 2 displayed in a position which corresponds to the set print scale. In step 48, the
 3 user can set a different print scale by actuating the control element. If he does
 4 that, the method returns to step 46 and carries out this step with the different
 5 print scale chosen by the user (and also the subsequent steps, if no further
 6 different print scale is chosen). In other words, the new slider position is
 7 displayed and a correspondingly modified graphical representation 5 of the page
 8 and the sheet splitting 6 is determined and displayed in the print preview
 9 window 3. The user can cancel the print preview dialog in step 49 or give a
 10 print command in step 50 by clicking on the print button 9. If he gives the print
 11 command, the print job is passed in step 51 to the operating system 32 by
 12 drawing the page into the GDI of the operating system 32. The steps described
 13 so far (steps 41 to 51) are performed by the application program 31. Then, in
 14 step 52, the operating system 32 passes the print job to the printer driver 33,
 15 which, in turn, passes it in step 53 to the communications port driver 34 which
 16 passes it in step 54 to the printer 24. The printer 24 prints the graphical
 17 representation 5 in a tile-like manner, as it was presented to the user in the
 18 print preview step 47.

19 FIG. 9 is a similar flow diagram which illustrates an implementation by
 20 the printer driver 33. Steps 61 to 64 correspond to steps 41 to 44 of FIG. 8. It
 21 should be noted, however, that the application program 31 generates the
 22 document page in step 61 based on a virtual sheet size, which is at least equal
 23 to the total size of the largest possible number of sheets to be used for the tile-
 24 like printing method. In the framework of the application program 31, the user
 25 cannot yet choose a print preview after step 64, as in step 45 of Figure 8.
 26 Rather, he can choose to progress with the print process in step 65. Then, in
 27 step 66, the print job is passed to the operating system 32, corresponding to
 28 step 51 of FIG. 8. In step 67, the operating system 32 passes the print job to
 29 the printer driver 33.

1 In the embodiment of FIG. 9, the printer driver 33 is responsible for the
 2 print preview functionality and carries out the "preview steps" 68 to 73 on the
 3 page which has been generated by the application program 31 assuming the
 4 virtual sheet size. These steps correspond to steps 45 to 50 of Figure 8 which
 5 have already been described in detail. After the preview steps, the printer driver
 6 33 passes the print job in step 74 to the communications port driver 33
 7 (corresponding to step 53), which, in turn, passes it in step 75 to the printer
 8 24 (corresponding to step 54). In summary, steps 61 to 66 are performed by
 9 the application program 31, step 67 is performed by the operating system 32,
 10 steps 68 to 74 are performed by the printer driver 33, step 75 is performed by
 11 the communications port driver 34. The printer 24 prints the graphical
 12 representation 5 in a tile-like manner, as it was presented to the user in the
 13 print preview step 70.

14 The program that implements the disclosed print preview method is an
 15 applet written in Java (Java is a trademark of Sun Microsystems, Inc.). It can
 16 likewise be written in any other suitable programming language, preferably in
 17 an object-oriented programming language. Figure 10 shows a diagram of the
 18 most relevant classes with the most relevant methods of the program. An outer
 19 dialog class of the print preview dialog is called *PrintDialog*. It contains the
 20 following items: i) The slider 8 which controls the scale of the content of the
 21 print preview window 3; ii) the print preview window 3 which shows the
 22 scaled preview. It is implemented by a class *PreviewPanel*. This class is an
 23 inner class of *PrintDialog* in order to have access to the member variables of
 24 the dialog. *PreviewPanel* represents the drawing area (i.e. the print preview
 25 window 3) in the print preview dialog.; iii) the print and cancel buttons 9, 10.
 26 They are instances of a class *JButton* (not shown).

27 The content of the print preview window 3 implements an interface
 28 *Pannable*. This interface provides the method that does the actual painting in
 29 the scale provided by the print preview window 3, the method *paintPanner*.

1 This method is responsible for drawing a scaled version of the document page
2 into a graphics using a particular scale (the graphics and the scale are passed
3 as input parameters). A class *MapView* is responsible for drawing the whole
4 graphical representation 5, for example, a network map in the print preview
5 window 3.

6 Thus, a general purpose of the disclosed embodiments is to provide an
7 improved method, computer system and computer program product for making
8 large printouts with note-format printers.

9 All publications and existing systems mentioned in this specification are
10 herein incorporated by reference.

11 Although certain methods, systems and products constructed in
12 accordance with the teachings of the invention have been described herein, the
13 scope of coverage of this patent is not limited thereto. On the contrary, this
14 patent covers all embodiments of the teachings of the invention fairly falling
15 within the scope of the appended claims either literally or under the doctrine of
16 equivalents.